

## **SECTION 1. Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

Product code : Hygienfresh Piumasoft  
Trades code : A45-020  
Product line: HygienFresh

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

Finissante for feathers with Detangling effect  
Sectors of use:  
Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against  
Do not use for purposes other than those listed

### **1.3. Details of the supplier of the safety data sheet**

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: [info@tintolav.com](mailto:info@tintolav.com) - Sito internet: [www.tintolav.com](http://www.tintolav.com)

Email tecnico competente: [a.conedera@tintolav.com](mailto:a.conedera@tintolav.com)

National contact: Malta: Emergency Ambulance 112  
Accident & Emergency Department 2545 4030

### **1.4. Emergency telephone number**

The UK National Poisons Emergency number +44 (0)870 600 6266  
London: Emergency 24 hour telephone +44 (0) 207188 0100

## **SECTION 2. Hazards identification**

### **2.1. Classification of the substance or mixture**

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:  
GHS07

Hazard Class and Category Code(s):  
Eye Irrit. 2, Aquatic Chronic 3

Hazard statement Code(s):  
H319 - Causes serious eye irritation.  
H412 - Harmful to aquatic life with long lasting effects.

If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.  
The product is dangerous to the environment as it is harmful to aquatic life with long lasting effects

### **2.2. Label elements**

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):  
GHS07 - Warning



**Hazard statement Code(s):**

- H319 - Causes serious eye irritation.
- H412 - Harmful to aquatic life with long lasting effects.

**Supplemental Hazard statement Code(s):**

EUH208 - Contains Hexyl salicylate,  $\alpha$ -Hexylcinnamaldehyde, Geraniol, 3-methyl-4-(2,6,6-trimethylcyclohex-2-enyl)but-3-en-2-one. May produce an allergic reaction.

**Precautionary statements:**

**General**

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.

**Prevention**

- P264 - Wash your hand thoroughly after handling.
- P273 - Avoid release to the environment.

**Response**

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

**Disposal**

P501 - Dispose of contents / container in accordance with local and national regulations.

**Contains:**

Steareth-21, propan-2-ol, Hexyl salicylate, 2-phenylethanol, alpha-Isomethyl ionone, 4-tert-Butylcyclohexyl acetate, Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, hydroxy-terminated, Isotridecanol, ethoxylated < 10 OE, 2-propylheptanol ethoxylated, propoxylated

**Contains (Reg.EC 648/2004):**

5% < 15% cationic surfactants, < 5% Dye, Miscela di: 5-cloro-2-metil-2H-isotiazol-3-one [EC no. 247-500-7]; 2-metil-2H-isotiazol-3-one [EC no, perfumes, non-ionic surfactants, Citronellol,  $\alpha$ -Hexylcinnamaldehyde, Geraniol, ALPHA ISOMETHYLE IONONE, BUTYLPHENYL METHYLPROPIONAL, Linalool, Isoeugenol

Content of VOC ready to use condition: 0,73 %

**2.3. Other hazards**

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

**SECTION 3. Composition/information on ingredients**

**3.1 Substances**

Irrilevant

**3.2 Mixtures**

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
Fatty acids, C10-20 and C16-18-unsatd., reaction products with triethanolamine, di-Me sulfate-quaternized	> 5 <= 10%	Skin Irrit. 2, H315; STOT SE 3, H335		91995-81-2	295-334-3	
Poly[3-((2-aminoethyl)amino)pro	> 1 <= 5%	Skin Irrit. 2, H315;		102782-92-3	600-354-1	

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
poly(methyl(dimethyl)siloxane, hydroxy-terminated		Eye Irrit. 2, H319				
Hexyl salicylate - FEMA 0	> 0,1 < 1%	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2, H319; Aquatic Acute 1, H400; Aquatic Chronic 1, H410		6259-76-3	228-408-6	01-2119638 275-36-000 2
Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides - FEMA 0	<= 0,1%	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 100 100		68424-85-1	270-325-2	
ethanol	<= 0,1%	Flam. Liq. 2, H225	603-002-00-5	64-17-5	200-578-6	

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

#### Direct contact with skin (of the pure product):

Take contaminated clothing immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

In case of contact with skin, wash immediately with water and soap.

#### Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

#### Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### Advised extinguishing agents:

Water spray, CO<sub>2</sub>, foam, dry chemical, depending on the materials involved in the fire.

#### Extinguishing means to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

---

## **5.2. Special hazards arising from the substance or mixture**

No data available.

## **5.3. Advice for firefighters**

Use protection for the breathing apparatus  
Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

## **SECTION 6. Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

Wear gloves and protective clothing

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear gloves and protective clothing

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

### **6.2. Environmental precautions**

Contain spill with earth or sand.

If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities.

Discharge the remains in compliance with the regulations

### **6.3. Methods and material for containment and cleaning up**

6.3.1 For containment:

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.

Prevent it from entering the sewer system.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

### **6.4. Reference to other sections**

Refer to paragraphs 8 and 13 for more information

---

## **SECTION 7. Handling and storage**

---

### **7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors  
At work do not eat or drink.  
Wear protective gloves/protective clothing/eye protection/face protection.  
See also paragraph 8 below.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep in original container closed tightly. Do not store in open or unlabeled containers.  
Keep containers upright and safe by avoiding the possibility of falls or collisions.  
Store in a cool place, away from sources of heat and `direct exposure of sunlight.

### **7.3. Specific end use(s)**

Industrial Manufacturing:  
Handle with extreme caution.  
Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):  
Handle with care.  
Store in ventilated place away from heat sources,  
Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):  
Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

## **SECTION 8. Exposure controls/personal protection**

### **8.1. Control parameters**

Related to contained substances:

ethanol:

Component CAS-No. Value Control parameters

Basis

Ethanol-17-64 TWA 5 ppm 1.000

1.920 mg/m<sup>3</sup>

UK. EH40 WEL-Workplace Exposure Limits

Remarks Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

- Substance: ethanol

DNEL

Systemic effects Long term Workers inhalation = 950 (mg/m<sup>3</sup>)

### **8.2. Exposure controls**

Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen

Private households (= general public = consumers):

No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):

No specific monitoring foreseen

Individual protection measures:

---

(a) Eye / face protection  
Not needed for normal use.

(b) Skin protection

(i) Hand protection  
Not needed for normal use.

(ii) Other  
Wear normal work clothing.

(c) Respiratory protection  
Not needed for normal use.

(d) Thermal hazards  
No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	viscous liquid	
Odour	characteristic	
Odour threshold	not determined	
pH	3 - 3.5	
Melting point/freezing point	not determined	
Initial boiling point and boiling range	not determined	
Flash point	>100°C	
Evaporation rate	irrelevant	
Flammability (solid, gas)	non flammable	
Upper/lower flammability or explosive limits	not determined	
Vapour pressure	not determined	
Vapour density	not determined	
Relative density	0,9	
Solubility	in water	
Water solubility	non determinato	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	not determined	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	not explosive	
Oxidising properties	non-oxidizing	

## 9.2. Other information

Content of VOC ready to use condition: 0,73 %

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

No reactivity hazards

### 10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

### 10.3. Possibility of hazardous reactions

There are no hazardous reactions

### 10.4. Conditions to avoid

Nothing to report

### 10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, inorganic sulfide, strong reducing agents.

It can generate toxic gases to contact with inorganic sulfide, strong reducing agents.

### 10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11. Toxicological information

### 11.1. Information on toxicological effects

ATE(mix) oral = 323.333,3 mg/kg

ATE(mix) dermal = ∞

ATE(mix) inhal = ∞

(a) acute toxicity: ethanol: LD50 Oral-rat-7.060 mg/kg

Remarks: Lungs, Thorax, or Respiration: Other changes.

LC50 Inhalation-rat-10:0-20000 ppm

(b) skin corrosion/irritation Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides: rabbit Result:

Method: DOT Corrosive Exposure time: 12:0 am

ethanol: Skin-rabbit

Result: Irritating to skin. -12:0 am

(c) serious eye damage/irritation: If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

ethanol: Eyes-rabbit

Result: Mild eye irritation-12:0 am

(Draize Test)

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides: rabbit Result: Caustic Method: DOT

(d) respiratory or skin sensitization: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:



Buehler guinea pig Test Classification: Did not cause sensitization on laboratory animals.

Result: not sensitizing Method: OECD Test Guideline 406

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: ethanol: Reproductive toxicity-Human-female-Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other measures or neonatal effects.

Effects on Newborn: Drug dependence.

(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.

(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.

(j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

Fatty acids, C10-20 and C16-18-unsatd., reaction products with triethanolamine, di-Me sulfate-quaternized:

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 13400

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, hydroxy-terminated:

LD50 (rat) Oral (mg/kg body weight) = 2000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

Hexyl salicylate:

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

LD50 (rat) Oral (mg/kg body weight) = 344

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 3340

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 5

ethanol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes and ingestion.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C.

Effects of short-term exposure: the substance is irritating to the eyes. Inhalation of high vapour can cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features. The substance may have an effect on the high central nervous system respiratory tract, causing irritation, headaches, fatigue and lack of concentration. See Notes.

ACUTE HAZARDS/Symptoms INHALATION Cough. Headaches. Fatigue. Drowsiness.

CUTE CUTE.

EYE Redness. Pain. Burning.

SWALLOWED burning sensation. Headaches. Confusion. Vertigo. State of unconsciousness.

NOT and consumption of ethanol during pregnancy can have adverse effects on the unborn child. Chronic ethanol ingestion can cause cirrhosis of the liver.

LD50 (rat) Oral (mg/kg body weight) = 7060

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 20000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 20000

## SECTION 12. Ecological information

### 12.1. Toxicity

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

Related to contained substances:

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, hydroxy-terminated:



EC50 (Water flea (Daphnia magna), 48 d): > 100 mg/l  
C(E)L50 (mg/l) = 100

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:  
C(E)L50 (mg/l) = 0,01 100  
100

ethanol:  
C(E)L50 (mg/l) = 11200

The product is dangerous for the environment as it is toxic for aquatic organisms following acute exposure.

Use according to good working practices to avoid pollution into the environment.

### **12.2. Persistence and degradability**

Related to contained substances:  
Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, hydroxy-terminated:  
BOD/COD ratio: 84.5% (OECD 302B/ISO 9888)

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:  
Biodegradability:  
OECD Confirmatory > 90% Test Method: OECD 303 A Modified SCAS Test Exposure time: 99% 7 d > Method: OECD Test 302 Evolution CO2 Concentration: 5 mg/litre Exposure time: 28 d Result: Readily biodegradable.  
95.5% Method: OECD 301 B

### **12.3. Bioaccumulative potential**

No data available.

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

### **12.6. Other adverse effects**

No adverse effects

## **SECTION 13. Disposal considerations**

### **13.1. Waste treatment methods**

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

## **SECTION 14. Transport information**

### **14.1. UN number**

Not included in the scope of application regulations concerning the transport of dangerous goods: by road (ADR); by rail (RID); by air (ICAO / IATA); by sea (IMDG).

### **14.2. UN proper shipping name**

None

### **14.3. Transport hazard class(es)**

None

### **14.4. Packing group**

None

### **14.5. Environmental hazards**

None

### **14.6. Special precautions for user**

No data available.

### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

It is not intended to carry bulk

## **SECTION 15. Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

REGULATION (EU) No 1357/2014 - waste:  
HP14 - Ecotoxic

### **15.2. Chemical safety assessment**

The supplier has made an assessment of chemical safety

## **SECTION 16. Other information**

### **16.1. Other information**

Points modified compared to previous release: 2.1. Classification of the substance or mixture, 2.2. Label elements, 2.3. Other hazards, 4.1. Description of first aid measures, 4.3. Indication of any immediate medical attention and special treatment needed, 5.1. Extinguishing media, 5.2. Special hazards arising from the substance or mixture, 6.2. Environmental precautions, 6.3. Methods and material for containment and cleaning up, 7.1. Precautions for safe handling, 7.2. Conditions for safe storage, including any incompatibilities, 8.1. Control parameters, 8.2. Exposure controls, 9.2. Other information, 10.4. Conditions to avoid, 11.1. Information on toxicological effects, 12.1. Toxicity, 12.2. Persistence and degradability, 13.1. Waste treatment methods, 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Description of the hazard statements exposed to point 3

- H315 = Causes skin irritation.
- H335 = May cause respiratory irritation.
- H319 = Causes serious eye irritation.
- H317 = May cause an allergic skin reaction.
- H400 = Very toxic to aquatic life.
- H410 = Very toxic to aquatic life with long lasting effects.
- H302 = Harmful if swallowed.
- H312 = Harmful in contact with skin.
- H314 = Causes severe skin burns and eye damage.
- H318 = Causes serious eye damage.
- H225 = Highly flammable liquid and vapour.

Classification based on data of all mixture components

Main normative references:

- Directive 1999/45/EC
- Directive 2001/60/EC
- Regulation 1272/2008/EC
- Regulation 2010/453/EC

\*\* The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.

---